



Router2

```
Router>en
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip add 192.168.0.62 255.255.255.240
Router(config-if)#no sh

%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to
up

Router(config-if)#int se0/0/0
Router(config-if)#ip add 192.168.0.45 255.255.255.252
Router(config-if)#no sh

Router(config-if)#ip route 192.168.0.48 255.255.255.240 fa0/0
Router(config)#ip route 192.168.0.44 255.255.255.252 se0/0/0
Router(config)#ip route 192.168.0.16 255.255.255.248 se0/0/0
Router(config)#ip route 192.168.0.0 255.255.255.240 se0/0/0
Router(config)#ip route 192.168.0.248 255.255.255.252 se0/0/0
Router(config)#ip route 192.168.0.252 255.255.255.252 se0/0/0
Router(config)#^Z
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#copy running-config startup-config
Destination filename [startup-config]?
Building configuration...
[OK]
Router#
```